

## Straight RJ-45 Coupler Cat 6A, shielded



### Applications

PAMix CAT6A coupler female to female connector strait (in-line) design. Used for data cables extension, consolidation point and patch panels. Fully shielded, fast speed up to 10Gbps, frequency up to 500 MHz.

### Construction

Brass C2680 T=0.25mm shield material, Phosphor bronze gold plated contact material, fireproof housing, 1.2mm PCB

### Technical Information

- Cat 6A 500MHz class EA performance
- RJ45 8P8C female connectors at both sides
- Tool free mounting in patch panels
- 1.2mm PCB
- 16.22 X 16.77 X 32.05 mm (H X W X D)
- Operating temperature -10 to 60 °C
- Storage temperature -40 to 70 °C
- Minimum 750 times insertion life time

### Standards

Meeting cable standards ISO/IEC 11801, EN 50173



### Ordering Information

Description	Article Number
Straight Cat 6A coupler, shielded	1005312

### Related Products

Description	Article Number
1U 24 ports Patch panel STM-1P	1005011
1U 24 port Patch panel, strain relief STM-ARM	1005002
1U 48 port Patch panel, strain relief STM-ARM	1005003
0.5U 24 port Patch panel, strain relief STM-ARM Metallic	1005006